

**PRODUCT INFORMATION**

<i>DESCRIPTION</i>	Dulux Professional Diamond A1000 Sheen is a premium quality paint with a smooth and sophisticated sheen finish. It is specially formulated with Colourguard technology that locks in colours to keep your wall looking beautiful for longer. Dulux Professional Diamond A1000 Sheen is certified to Singapore Green Labelling Scheme (032-059-0582).
<i>BENEFITS</i>	<ul style="list-style-type: none"> <li>• Classic smooth sheen finish with glow of pearl and feel of silk</li> <li>• Colourguard technology that locks in colours</li> <li>• Outstanding washable surface</li> <li>• Low odour Low VOC</li> </ul>
<i>USAGE</i>	Ideal for new and previously painted interior masonry, plaster, and building boards surfaces.
<i>PACK SIZE</i>	20 litres
<i>COLOUR RANGE</i>	Refer to Colour Collaterals
<i>PRODUCT CODE</i>	A913

**PHYSICAL FILM PROPERTIES**

<i>Water Resistance</i>	Resistant to the levels of atmospheric humidity present in normal interior environments. Not suitable for use on immersed surfaces or where there is heavy and prolonged condensation.
-------------------------	--

**PRODUCT DATA**

<i>Composition</i>	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders Binder : Vinyl Acrylic Emulsion Solvent : Water
<i>Volume Solid</i>	White 35% (nominal), other colours will vary.
<i>Drying Time</i>	Single coat at standard thickness:
<i>Touch Dry</i>	Dependent on temperature and humidity
<i>Recoat</i>	2 - 4 hours
<i>Theoretical Film Thickness</i>	Dry: 30 - 40 microns
<i>Theoretical Coverage</i>	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 10.5 - 11.5 m <sup>2</sup> /litre.
<i>Finishing</i>	Sheen

**CERTIFICATE**



**APPLICATION GUIDE**

*Surface Preparation*

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. Remove all loose and defective paint or powdery residues by thorough brushing and scraping, using a stiff fiber brush. Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Treat any areas affected by mould, lichens, algae and moss with Dulux Professional Fungicidal Wash. Repair any surface defects with an appropriate filler. Surfaces that remain powdery, friable or chalky after thorough preparation should be sealed with one coat of an appropriate Sealer (see below System Recommendation). Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust. Do not paint if the wall is saturated with dampness. (Protimeter reading higher than 16%). Allow excess moisture to evaporate.

*Application Tools*

By roller, brush or conventional/airless spray.

*Dilution*

Ready to use. Dilute up to 10% with potable water when necessary if application by brush or roller. For conventional spray application, thin up to 30%.

Note: Excessive dilution from that recommended will result in low coverage and may impact application properties and colour.

*System Recommendation*

Substrate	Sealer (1 coat)	Topcoat (2 coats)
New wall surface	Dulux Professional Diamond Sealer A1000	Dulux Professional Diamond A1000 Sheen
Old wall surface	Dulux Professional Diamond Solventbased Sealer A1000	

*For alternative coating systems, please refer to our Sales Representative*

*Cleaning Up*

Clean all equipment with clean water immediately after use.

**HEALTH, SAFETY &  
ENVIRONMENT INFORMATION**

Please refer to Product Safety Data Sheet



Akzo Nobel Paints (Singapore) Pte Ltd  
AkzoNobel House, 3 Changi Business Park Vista  
#05-01, Singapore 486051  
Tel: (65) 6265 0677 Fax: (65) 6265 4775  
Email: [customer.care.sg@akzonobel.com](mailto:customer.care.sg@akzonobel.com)  
Website: [www.duluxprofessional.com.sg](http://www.duluxprofessional.com.sg)